

A close-up, low-angle shot of a man's face and neck, tilted back with his eyes closed. He is in a steam bath, with steam rising from the bottom of the frame. The background consists of light-colored, vertically-oriented tiles. The lighting is soft and warm, highlighting the texture of his skin and the steam.

STEAMIST®

COMMERCIAL STEAMBATH SYSTEMS
PRODUCT CATALOG AND U.S. PRICE LIST | MAY 2017

Commercial Steambath Systems

Steamist offers a complete selection of Steam Generators, Controls and Accessories for steamrooms in commercial applications. In commercial environments it's particularly important to be able to program a Steam Generator for energy-efficiency and reduced costs during off-peak hours.

HC SERIES STEAM GENERATORS INCLUDE OUR DIGITAL CONTROL PACKAGE.

- + Allows programming of steamroom settings from up to 100-foot distance from generator (50-foot cables ship standard).
- + Idle setback feature allows efficient tailoring of operations for off-peak hours. Each day of the week can be programmed individually. Provides maximum temperatures and energy-saving "idle" temperatures.
- + When installed with Second Room Package, can program two steamrooms with one generator.



Package includes:

- + Microprocessor Boiler Control with two relays prewired for the aromatherapy pump
- + Digital Command Center and cable
- + User Bypass Control and cable
- + Room Sensor and cable
- + Steam Solenoid pre-assembled to the steam generator

Optional Second Room Package Available



HC Series Generators come with Steamist's 3199 Steamhead, with Cool Sense silicone cover.





Steamist, Inc. is proud to be an ASME Authorized Certificate Holder. All of our HC Series Steam Generators are certified and stamped to meet stringent ASME codes and UL standards.



MODELS HC-9/12/15/18/24
Dimensions: 21"L x 19"W x 25"H



MODELS HC-30/36/48
Dimensions: 39"L x 22"W x 28"H

HC SERIES STEAM GENERATORS									
MODEL	PRICE	kW	MAX CU FT	PRODUCT CODE	ELECTRICAL				WEIGHT
					VOLTS	PHASE	AMPS	BREAKER*	
HC-9	\$6,400	9	400	60900	240	1	38	50	200 lbs
				60901	208	1	43	60	
				60902	240	3	22	30	
				60903	208	3	25	35	
				60904	480	3	11	15	
HC-12	\$6,700	12	500	61200	240	1	50	70	200 lbs
				61201	208	1	58	80	
				61202	240	3	29	40	
				61203	208	3	33	45	
				61204	480	3	15	20	
HC-15	\$7,000	15	620	61500	240	1	63	80	200 lbs
				61501	208	1	72	90	
				61502	240	3	36	45	
				61503	208	3	42	60	
				61504	480	3	18	25	
HC-18	\$7,200	18	740	61800	240	1	75	100	200 lbs
				61801	208	1	87	110	
				61802	240	3	43	60	
				61803	208	3	50	70	
				61804	480	3	22	30	
HC-24	\$7,900	24	1000	62400	240	1	100	125	200 lbs
				62401	208	1	115	150	
				62402	240	3	58	80	
				62403	208	3	67	90	
				62404	480	3	29	40	
HC-30	\$9,000	30	1250	63000	240	1	125	175	300 lbs
				63001	208	1	144	200	
				63002	240	3	72	90	
				63003	208	3	84	110	
				63004	480	3	36	45	
HC-36	\$9,600	36	1500	63600	240	1	150	200	300 lbs
				63601	208	1	173	225	
				63602	240	3	87	110	
				63603	208	3	100	125	
				63604	480	3	44	60	
HC-48	\$10,100	48	2000	64802	240	3	116	150	300 lbs
				64803	208	3	133	175	
				64804	480	3	58	80	

*Note: 90°C copper wire is required for connection to the steam generator.

Auxiliary Manual Reset Pressure Cutoff is now standard on all Steamist Commercial HC Series Generators to meet UL 834 and ASME CSD-1 standards. Many state and local codes require an auxiliary pressure cutoff device with a manual reset.

HC Steam Generator Controls and Accessories

USER BYPASS CONTROL INCLUDED IN HC SERIES PACKAGES



User Bypass Control installed outside steamroom allows user to change settings within programmed temperature range.



A



B

Optional Second Room Package

Includes 2nd User Bypass Control with 50' cable, 2nd Room Sensor with 50' cable, 2nd Steam Solenoid pre-assembled to the steam generator, 2nd Steamhead.

SRP Second Room Package

\$600 | 68010 (not sold separately)

Pure Aromatherapy Oils (Optional)

For use only with our AP-100 Aroma Pump System. 1100 ml of essential oils, equivalent to competitors' 10L/2.6 gal. diluted spa oils commonly found on the market.

Essential Eucalyptus Oil (1100 ml)

\$250 | HC-EUC 68018

Essential Lavender Oil (1100 ml)

\$350 | HC-LAV 68019

A. Optional Aroma Pump System

The Steamist AP-100 is unique to the industry. It is a micro-dosing pump designed to work with pure essential oils. Most pump systems on the market today deliver a higher volume of diluted oils. Since oil does not mix with water an emulsifier chemical is used to help dilute the oil. The AP-100 delivers the full therapeutic value of pure essential oils without emulsifiers and dilution agents. Diluted oils are typically oils just 5% or 10% oil. Our 1100 ml bottles of pure essential oil deliver more oil than the typical 10 liters/2.6 gallons of diluted oil commonly sold.

4" W x 18" H x 4.5" D

AP-100 Commercial Aroma Pump System

\$1,000 | 68017

B. Programmable Steamroom Temperature Alert

Digital display with audible alert, secondary remote audible alert, tamperproof lock, heater interrupt relay and test button. Lock feature prevents patrons from changing the temperature setpoint, prevents the alert from sounding and prevents the heat from being cut off. The alert cannot be reset until the room cools down below the programmed temperature. Interrupt relay disables heater when the audible alarm sounds. Test button is used to check that the heater is disabled when alert sounds.

6.5" W x 7" H x 1.75" D

TA-100 Temperature Alert

\$945 | 68016



C

C. Digital Automatic Blowdown Valve

DC-ABD, 208V Valve
 \$650 | 68014 (not sold separately)

DC-ABD, 240/480V Valve
 \$650 | 68015 (not sold separately)

Auxiliary Manual Reset Low-Water Control

Many states and local jurisdictions, as a standard, require an independent, manual reset, second low-water cutoff control. Please check with your local jurisdiction if this needs to be ordered together with the HC steam generator. (This is a factory-installed option and cannot be sold without a Steam Generator.)

\$650 | 68020 (not sold separately)



D

D. Optional 24" Stand for HC Series Steam Generators

\$400 | 68005
 HC-9 through HC-24.
 20" L x 10-1/2" W x 24" H

\$475 | 68006
 HC-30 through HC-48.
 25-1/2" L x 14" W x 24" H



E

E. ASME Code Blowdown Tank

Permits draining of hot boiler water into the tank before it is dumped into drainage system.

Allows the HC blowdown system to comply with codes prohibiting discharge of water exceeding 140°F.

\$2,500 | 68007